



PRESSURE GAUGES — PX SERIES

For oxygen / acetylene purpose (Use-No-Oil gauges)

These gauges are designed for welding, medical and compressed air services. Strictly oil-free controlled in production. Constructed with stainless steel case brass connection.



"A"



"B"

Size (mm)	Type	Connection Part (BSPM)	Standard Pressure Range
50	A, B	1/8"	0 To 300 Bar & PSI
60	A, B	1/4"	0 To 3 Bar & PSI
60	A, B	1/4"	0 To 25 Bar & PSI
60	A, B	1/4"	0 To 35 Bar & PSI
60	A, B	1/4"	0 To 250 Bar & PSI
60	A, B	1/4"	0 To 400 Bar & PSI



PREASSURE GAUGES — CGB SERIES

(Capsule gauges)

The CGB series pressure gauges are mainly use for measurements of very low pressure. Constructed in AISI304 / Chrome brass case, these gauges have a very special diaphragm movement which reacts sensitively to very low pressure.



"A"



"B"



"BD"

Size (mm)	Type	Connection Part (NPTM)	Standard Pressure Range
63	A, B	1/4"	-1000-0+1000, 2000, 3000, 5000 mmH2O / mbar
100	A, B	3/8"	-2000-0+2000 mmH2O / mbar
100	A, B	3/8"	-3000-0+3000 mmH2O / mbar
100	A, B	3/8"	-500-0+500 mmH2O / mbar

