



Temperature Calibrator (TESZ - TTC20650)

Applications:

Ideal for quick/ fast site calibration of RTD's / T/C's,
Bi-Metal Thermometers, Temperature Switches / Indicators, etc.

Features:

- Heavy Duty
- Rugged Field Use/ Calibration at Site
- No Dangerous Liquids/ Fumes
- Fast and Reliable
- Improved Accuracy/ Resolution/ Stability
- Interchangeable Thermowell Inserts
- Beach Top with Carrying Handle
- Traceable Calibration Certificate Included
- Optional leather carrying case



Detail Specifications

Maker	TESZ®
Model	TTC20650
Range	20 Deg. C above ambient to 650 Deg. C
Resolution	0.1 Deg. C
Accuracy	+/- 1.5 Deg. C
Stability	+/- 0.5 Deg. C
Stabilization Time	15 Minutes
Well Diameter	25 mm
Well Dept	120mm
Heating Time (to Max.)	20 minutes
Cooling Time (to 100°C)	50 minutes
Thermowell (Interchangeable Type)	¼" & ½" Bore Diameter Standard Other Sizes available Upon Request
Switch Test Facility/ Supply	Provided / 5 VDC (open)
Power Consumption	1100 Watts
Power Supply	Special Design Selectable Switch (220 VAC / 110 V)
Instrument Dimensions	270x124x325mm
Instrument Weight	Approx. 8 kg

(TC.VI Aug 2017.)