



HYDROMETER - HSG SERIES (Hydrometers)

Applications:

Hydrometers are instruments normally use for measuring density of medium like seawater, petroleum, light / heavy oil, etc.

Specifications:

Type / Purpose	Range (gr/cm3)	Length	Material	Calibrated temp.	Others
Seawater	1.000-1.040	200mm, 250mm	Glass, Chrome brass	TP. 20 Deg. C	-
Draft survey	0.990-1.040	330mm	Glass	TP. 15 Deg. C, TP. 20 Deg. C	C/w factory conformity certificate
API	01+11API,..... 89+101API	330mm	Glass	TP. 20 Deg. C	-
ASTM	0.600-0.650 1.050-1.100	250mm, 330mm	Glass	TP. 15 Deg. C	-
Specify gravity	0.600-0.700, 1.500-1.600	300mm	Glass	TP. 20 Deg. C	-
Light oil	0.700-0.850, 0.850-1.000, 1.000-1.200	300mm	Glass	-	-
Anti-freeze tester	A-K	-	Glass & Plastic	TP. 20 Deg. C	-
Boiler water	0-4/32	250mm	Glass	TP. 90 Deg. C	-



** Non-standard specifications from above can be customize on indent basis.

***All information subject to changes without prior notice owing to continuous development.