




# Pressure Gauges (PG series - General Purpose Gauges)

## Applications:

These glycerine filled pressure gauges are for pressure or vacuum applications where high-frequency pressure fluctuations, surges or vibrations are present, constructed with corrosion resistant stainless steel case, bronze ( or phosphor bronze) bourdon tube, bronze movement and mounting parts.

Fully stainless steel case, connection and movement constructed pressure gauges suitable for anti-corrosive / ammonia purposes are also available.


## Specifications:



"A"




"B"




"AD"



"AD"



"BD"



"BRACKET MOUNT"

| Size (mm) | Type                        | Connection Part (BSPM) | Standard Pressure Range     |
|-----------|-----------------------------|------------------------|-----------------------------|
| 40        | A, B, AD, BD                | 1/8"                   | 76cmHg Vac...100 Bar & PSI  |
| 50        | A, B, AD, BD                | 1/8"                   | 76cmHg Vac...100 Bar & PSI  |
| 60        | A, B, AD, BD, BRACKET MOUNT | 1/4"                   | 76cmHg Vac...1000 Bar & PSI |
| 75        | A, B, AD, BD                | 1/4" , 3/8"            | 76cmHg Vac...1000 Bar & PSI |
| 100       | A, B, AD, BD                | 3/8" , 1/2"            | 76cmHg Vac...2500 Bar & PSI |
| 150       | A, B, AD, BD                | 3/8"                   | 76cmHg Vac...2500 Bar & PSI |



\*\* Non-standard specifications from above can be customize on indent basis.

\*\*\*All information subject to changes without prior notice owing to continuous development.