



# Thermometers

## TB SERIES (Bi-Metal industrial thermometers)



### Specifications:

<b>Dial (mm)</b>	<b>50, 63, 75, 100, 130, 150</b>
<b>Case</b>	AISI 304 stainless steel
<b>Bezel</b>	AISI 304 stainless steel, hermetically sealed or detachable
<b>Range</b>	From -80 Deg. C&F.....550Deg. C&F
<b>Type</b>	Vertical (Straight), Horizontal (Rear), Adjustable angle
<b>Stem</b>	AISI 304 stainless steel
<b>Stem length</b>	From 30mm..... 300mm
<b>Stem diameter</b>	6mm, 8mm, 10mm
<b>Connection</b>	1/4" NPT standard on 50mm dial, fixed centre back and bottom 1/2" NPT standard on 75mm, 100mm, 130mm, 150mm available,
<b>Lens</b>	Glass standard, shatterproof glass len is available
<b>Pointer</b>	Aluminum, painted black
<b>Movement</b>	Bi-metal coil
<b>Accuracy</b>	+/- 1.5% full scale standard, +/- 1.0% full scale available
<b>Other</b>	With recalibrator-reset screw or without

\*\* Non-standard specifications from above can be customize on indent basis.

\*\*\*All information subject to changes without prior notice owing to continuous development.